



WASTE HAULER AGREEMENT

The City of Victoria has issued me a copy of the State Law for Liquid Waste Transporters, as well as a copy of City Code Sections 13-105 – 13-135 (Direct Sewage Dumping, Industrial Waste Discharge and Generators of Grease and Grit Trap Waste).

The City code requires that all grease and grit traps be **completely** evacuated and State Law requires complete evacuation within 24 hours each time they are serviced. When a Waste Hauler engages in the cleaning of private service lines for grease or grit trap customers, this waste **may not** be introduced into the City's sanitary sewer mains. The City Code prohibits the introduction of grease or grit waste in quantities that will require unusual attention or expense associated with their clean up in the City sanitary sewer system.

The Victoria Regional Waste Water Treatment Plant is not licensed to accept **grease trap waste**. **Please refer to the enclosed list of licensed grease trap waste receiving facilities and the list of the wastes that are accepted at the Treatment Plant.**

I have read and understand these requirements. I understand the failure to comply with City Code could result in the revocation of my license to dispose of liquid wastes at the Victoria Regional Waste Water Treatment Plant.

Owner's Signature: _____

Printed Name of Owner: _____

Name of Company: _____

Mailing Address: _____

Physical Address: _____

Phone: _____ Fax: _____ E-mail: _____

Emergency contact person and phone: _____

Provide a complete list of trucks, including capacities for each, license numbers, permit numbers and expiration dates. (Local and State)

Waste haulers disposing of liquid wastes at the Victoria Regional Wastewater Treatment Plant must comply with all Local, State and Federal laws. The City of Victoria has developed additional requirements that will need to be complied with in order to dispose of liquid wastes. The Victoria Regional Wastewater Treatment Plant does not accept grease trap waste. The following requirements are mandatory.

1. Site gauges shall be clearly marked in gallons that indicate at least 4 equal measurements, including the minimum gauge level and full level on the gauge.
2. Truck number and maximum holding capacity shall be clearly marked on the driver and passenger side of each truck.
3. When evaluating the amount of solids and grease in the trap, the manifests shall indicate the percentage of each so that the City can determine if the facility needs its trap cleaning schedule modified. If the trap dimensions are unknown, the hauler should use their best judgment. The contents shall be marked in percentages only.
4. When making more than one load from the same trap, it shall be indicated in the upper right hand corner of the manifest that each load is what part of the total evacuation. (Example 1of 2, 2of 2)
5. Manifests shall be complete and legible. Multiple locations **cannot** be listed on the same manifest. Disposal may be denied for incomplete and/or illegible manifests or for manifests that list multiple locations. A signature from the POTW operator **must be** obtained accepting the load prior to disposal.
6. The vehicle must be constructed, operated, and maintained to prevent leakage of any wastes.
7. All discharge valves and ports must be prominently marked, visible and readily accessible.
8. Inlet and outlet openings must be constructed and located so that the liquid wastes will not leak, run or spill.
9. Hoses, tank valves, pumps, cylinders, pipe connections and other appurtenances must be maintained in good operating condition and free from leaks. Safety plugs shall be provided for each inlet and outlet tank valve.
10. The vehicle exterior shall be kept clean, vector and odor free and the interior of the tank should be washed as necessary.
11. Mixing of incompatible wastes within the same tank is prohibited.
12. All loads of domestic sludge destined for treatment at the belt press will require a 24 hour notification to be accepted.

In the event of a liquid waste spill during collection, transport or disposal, the Transporter shall **immediately** notify the Victoria Regional Wastewater Treatment Plant at 361/ 485-3620 and the City of

Victoria Public Works Department at 361/ 485-3381. Notifications under this section shall at a minimum, provide the following:

- A. Time and date the spill occurred.
- B. Amount spilled.
- C. Location of spill.
- D. Type of spill.
- E. Any corrective actions taken by the Transporter.
- F. Any other conditions that would indicate the need for an Emergency Spill Response Team.

The Transporter shall take any action required by State, Federal or local officials having jurisdiction, so that the spill will not present a public health or environmental hazard.